



ClareVision 8MP Motorized Varifocal IP Turret Camera, 2.7-13.5 mm, Starvis, WDR, (White | Black)

CLR-V200-8TVFW | CLR-V200-8TVFB



The 8MP Performance Series Turret Camera features a 4K Sony® Starvis[™] sensor and includes a 2.7-13.5 mm motorized varifocal lens with autofocus. The camera supports IR night vision up to 25 meters, micro SD card support for local storage up to 512 GB, and features an IP67 rated housing to protect the camera from outside elements.

Performance Highlights:

- Crystal clear video with 8MP 4K Sony® Starvis™ image sensor with 3840 x 2160 maximum recording resolution
- 2.7-13.5 mm motorized varifocal lens with built-in autofocus
- Micro SD card support up to 512 GB
- Infrared night vision up to 25 meters
- IP67 rated ingress protection against weathering elements and vandalism
- ClareOne and Control4 driver support
- Features 3D DNR and True WDR
- · Available in white and black color variations
- NDAA Compliant

Camera Parameters Image sensor Sensor type Sony® Starvis™ Lens 2.7 - 13.5 mm motorized varifocal lens with autofocus Aspect ratio Minimum illumination 0.01 Lux, F1.6 - F3.3 Field of view 103°-129° horizontal Video Parameters Streams Main stream: Up to max resolution H.265+, H.265, H.264+, H.264, 30 FPS, 5ub stream: 1280 x 720 @ 30 FPS, Tertiary: 352 x 288 @ 30 FPS Frame rate 3840 x 2160 @ 30 FPS, 3072 x 2048 @ 30 FPS, 1920 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1920 x 1080 @ 30 FPS, 2560 x 1440 @ 30 FPS, 1920 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 w 1090 w		
Image sensor Sensor type Lens 2.7 -13.5 mm motorized varifocal lens with autofocus Aspect ratio 16:9 Minimum illumination O.01 Lux, F1.6 - F3.3 Field of view 103°-129° horizontal Video Parameters Streams Main stream: Up to max resolution H.265+, H.265, H.264+, H.264, 30 FPS, Sub stream: 1280 x 720 @ 30 FPS, Tertiary: 352 x 288 @ 30 FPS Frame rate 38:40 x 2160 @ 30 FPS, 500 x 1440 @ 30 FPS, 1920 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS,	Specifications	
Sensor type Lens 2.7 -13.5 mm motorized varifocal lens with autofocus Aspect ratio 16:9 Minimum illumination 0.01 Lux, F1.6 - F3.3 Field of view 103°-129° horizontal Video Parameters Streams Main stream: Up to max resolution H.265+, H.265, H.264+, H.264, 30 FPS, Sub stream: 1280 x 720 @ 30 FPS, Tertiary: 352 x 288 @ 30 FPS Frame rate 3840 x 2160 @ 30 FPS, 3072 x 2048 @ 30 FPS, 1920 x 1080 @ 30 FPS, 1256 @ 30 FPS, 1200 x 1080 @ 30 FPS, 1250 x 480 @ 30 FPS Mirror mode Yes Snapshot Yes IR range 25 m (82 ft) IR auto switch IR wavelength 850 nm Backlight compensation Yes WDR Tue WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T), POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight Compliance	Camera Parameters	
Sensor type Lens 2.7 -13.5 mm motorized varifocal lens with autofocus Aspect ratio 16:9 Minimum illumination 0.01 Lux, F1.6 - F3.3 Field of view 103°-129° horizontal Video Parameters Streams Main stream: Up to max resolution H.265+, H.265, H.264+, H.264, 30 FPS, Sub stream: 1280 x 720 @ 30 FPS, Tertiary: 352 x 288 @ 30 FPS Frame rate 3840 x 2160 @ 30 FPS, 3072 x 2048 @ 30 FPS, 1920 x 1080 @ 30 FPS, 1256 @ 30 FPS, 1200 x 1080 @ 30 FPS, 1250 x 480 @ 30 FPS Mirror mode Yes Snapshot Yes IR range 25 m (82 ft) IR auto switch IR wavelength 850 nm Backlight compensation Yes WDR Tue WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T), POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight Compliance	Image sensor	8MP (3840 x 2160 @ 30 FPS)
Lens 2.7-13.5 mm motorized varifocal lens with autofocus Aspect ratio 16.9 Minimum illumination 0.01 Lux, F1.6 - F3.3 Field of view 103°-129° horizontal Video Parameters Streams Main stream: Up to max resolution H.265+, H.265, H.264+, H.264, 30 FPS, Sub stream: 1280 x 720 @ 30 FPS, Tertiary: 352 x 288 @ 30 FPS Frame rate 3840 x 2160 @ 30 FPS, 3072 x 2048 @ 30 FPS, 2592 x 1536 @ 30 FPS, 1280 x 720 @ 30 FPS, 1290 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1220 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 720 x 480 @ 30 FPS Mirror mode Yes Snapshot Yes IR range 25 m (82 ft) IR auto switch Yes IR wavelength 850 nm Backlight compensation Yes WDR True WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T), POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance		,
Minimum illumination 0.01 Lux, F1.6 - F3.3 Field of view 103°-129° horizontal Video Parameters Streams Main stream: Up to max resolution H.265+, H.265, H.264+, H.264+, H.264, 30 FPS, Sub stream: 1280 x 720 @ 30 FPS, Tertiary: 352 x 288 @ 30 FPS Frame rate 3840 x 2160 @ 30 FPS, 3072 x 2048 @ 30 FPS, 2592 x 1536 @ 30 FPS, 1280 x 720 @ 30 FPS, 1920 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 720 x 480 @ 30 FPS Mirror mode Yes Snapshot Yes IR range 25 m (82 ft) IR auto switch Yes IR wavelength 850 nm Backlight compensation Yes WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T), POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	, .	2.7 -13.5 mm motorized varifocal lens with autofocus
Minimum illumination 0.01 Lux, F1.6 - F3.3 Field of view 103°-129° horizontal Video Parameters Streams Main stream: Up to max resolution H.265+, H.265, H.264+, H.264+, H.264, 30 FPS, Sub stream: 1280 x 720 @ 30 FPS, Tertiary: 352 x 288 @ 30 FPS, 2592 x 1536 @ 30 FPS, 1300 FPS, 1920 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 1280 x 720 @ 30 FPS, 1920 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 720 x 480 @ 30 FPS Mirror mode Yes Snapshot Yes IR range 25 m (82 ft) IR auto switch Yes IR wavelength 850 nm Backlight compensation Yes WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T), POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Aspect ratio	16:9
Video Parameters Streams		0.01 Lux, F1.6 - F3.3
Streams Main stream: Up to max resolution H.265+, H.265, H.264+, H.264, 30 FPS, Sub stream: 1280 x 720 @ 30 FPS, Tertiary: 352 x 288 @ 30 FPS Frame rate 3840 x 2160 @ 30 FPS, 3072 x 2048 @ 30 FPS, 2592 x 1536 @ 30 FPS, 2560 x 1440 @ 30 FPS, 1920 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 720 x 480 @ 30 FPS Mirror mode Yes Snapshot Yes IR range 25 m (82 ft) IR auto switch Yes IR wavelength 850 nm Backlight compensation Yes WDR True WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T) , POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Field of view	103°-129° horizontal
H.264+, H.264, 30 FPS, Sub stream: 1280 x 720 @ 30 FPS, Tertiary: 352 x 288 @ 30 FPS Frame rate	Video Parameters	
1536 @ 30 FPS, 2560 x 1440 @ 30 FPS, 1920 x 1080 @ 30 FPS, 1280 x 720 @ 30 FPS, 720 x 480 @ 30 FPS Mirror mode Yes Snapshot Yes IR range 25 m (82 ft) IR auto switch Yes IR wavelength Backlight compensation Yes WDR True WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T), POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight Compliance	Streams	H.264+, H.264, 30 FPS, Sub stream: 1280 x 720 @ 30
Snapshot Yes IR range 25 m (82 ft) IR auto switch Yes IR wavelength 850 nm Backlight compensation Yes WDR True WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T) , POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Frame rate	1536 @ 30 FPS, 2560 x 1440 @ 30 FPS, 1920 x 1080 @
IR range 25 m (82 ft) IR auto switch Yes IR wavelength 850 nm Backlight compensation Yes WDR True WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T) , POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Mirror mode	Yes
IR auto switch IR wavelength Backlight compensation WDR True WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T), POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) S.0 x 5.25 in (127.0 x 133.35 mm) Weight Compliance	Snapshot	Yes
IR wavelength 850 nm Backlight compensation Yes WDR True WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T) , POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	IR range	25 m (82 ft)
Backlight compensation Yes WDR True WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T) , POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	IR auto switch	Yes
WDR DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T) , POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) S.0 x 5.25 in (127.0 x 133.35 mm) Weight Compliance	IR wavelength	850 nm
DNR 3D DNR Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T) , POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Backlight compensation	Yes
Audio Parameters Audio input/output Audio in, out (RCA) Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T) , POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	WDR	True WDR
Audio input/output Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T) , POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight Compliance	DNR	3D DNR
Event Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T) , POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) S.0 x 5.25 in (127.0 x 133.35 mm) Weight Compliance	Audio Parameters	
Motion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T) , POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight Compliance	Audio input/output	Audio in, out (RCA)
detection, intrusion, people gather) Network Parameters Ethernet RJ-45 (10/100Base-T) , POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Event	
Ethernet RJ-45 (10/100Base-T), POE IEEE 802.3af General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Motion detection	
General Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Network Parameters	
Alarm input/output 1/1 Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Ethernet	RJ-45 (10/100Base-T) , POE IEEE 802.3af
Local storage Supports up to 512 GB SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	General	
SD card included No Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Alarm input/output	1/1
Browser support Chrome, Edge Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Local storage	Supports up to 512 GB
Drivers Control4, Clare Controls Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	SD card included	No
Power DC 12V, 1100MA, POE (802.3af) Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Browser support	Chrome, Edge
Color White, black Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Drivers	Control4, Clare Controls
Weather rating IP67 Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Power	DC 12V, 1100MA, POE (802.3af)
Operating temperature -22° to 131° F (-30° to 60° C) Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Color	White, black
Dimensions (H x D) 5.0 x 5.25 in (127.0 x 133.35 mm) Weight 3.74 lb (1700 g) Compliance	Weather rating	IP67
Weight 3.74 lb (1700 g) Compliance	Operating temperature	-22° to 131° F (-30° to 60° C)
Compliance	Dimensions (H x D)	5.0 x 5.25 in (127.0 x 133.35 mm)
· · · · · · · · · · · · · · · · · · ·	Weight	3.74 lb (1700 g)
· · · · · · · · · · · · · · · · · · ·	Compliance	
		ETL/ETL-C, IC, CE, FCC, ROHS, ONVIF S/T

By making technology simple, Clare provides exclusive benefits to integrators, builders, and end users. We offer innovative smart home and business solutions, wireless security, controllable lighting, and IP CCTV components. For more information, visit www.clarecontrols.com.